IMBA-C2360-i2

ATX motherboard supports 14nm LGA1151 Intel® Xeon® E3 v5 series, Core™ i3, Pentium®, Celeron® processor per Intel® C236, DDR4, triple independent display, HDMI 2.0, dual Intel® PCIe GbE, USB 3.0, SATA 6Gb/s, HD Audio, IPMI 2.0 and RoHS



Dual BIOS (for flexible I/O only)

New

Easy for customer to switch different ME firmware to achieve I/O flexibility





Specifications

- CPU
  LGA1151 6th generation Intel® Xeon® E3-1200 v5, Core™ i3, Pentium® and Celeron® processor
- Chipset
  Intel® C236
- Memory
  Four 288-pin 2133 MHz dual-channel DDR4 SDRAM ECC and non-ECC unbuffered DIMMs support up to 64 GB
- BIOS
  UEFI BIOS
- Graphics Engine
  Intel® HD Graphics Gen 9 engine with 16 low-power execution units, supports DX11/12, OpenGL 4.3/4.4 and OpenCL2.x, ES 2.0
- Display Output
  Triple independent display
  1 x VGA (up to 1920x1200@60Hz)
  1 x DVI-D (up to 1920x1200@60Hz)
  1 x HDMI 2.0 (up to 4096x2160@60Hz)
  1 x iDP interface for HDMI, LVDS, VGA, DVI, DP (up to 4096x2304@60Hz)
- Ethernet
  LAN1: Intel® I219LM PCIe controller
  LAN2: Intel® I210AT PCIe with Intel® AMT 11.0 support
- External I/O Interface
  2 x USB 2.0
  4 x USB 3.0
- Internal I/O Interface
  1 x KB/MS (1x6 pin)
  1 x LPT (2x13 pin, P=2.54)
  1 x USB 3.0 (2x10 pin, P=2.0)
  2 x RS-232/422/485 (2x5 pin, P=2.54)
  4 x RS-232 (2x5 pin, P=2.0)
  4 x USB 2.0 (2x4 pin, P=2.0)
  6 x SATA 6Gb/s (RAID 0/1/5/10 supported)
- SMBus: 1 x SMBus (1x4 pin)
- I²C: 1 x I²C (1x4 pin)
- TPM: 1 x TPM (2x10 pin)
- Audio
  Realtek ALC662 HD codec supports 5.1-channel
  3 x Audio jacks (line-out, line-in, mic-in) on rear IO
  1 x Front audio (2x5 pin)
- Front Panel
  1 x Front panel (2x7 pin, power LED, HDD LED, speaker, power button, reset button)
- LAN LED: 2 x LAN LED (1x2 pin)
- Expansion
  1 x Full-size PCIe Mini card slot (support mSATA)
  2 x PCI slot
  2 x PCIe x8 slot (Gen3)
  3 x PCIe x4 slot (Gen3)
- iRIS Remote Management Module: 1 x iRIS-2400 slot
- Watchdog Timer: Software programmable supports 1~255 sec. system reset
- Digital I/O: 8-bit digital I/O (2x5 pin)
- Fan Connector
  1 x CPU smart fan (1x4 pin)
  2 x System smart fan (1x3 pin)
- Power Supply: ATX/AT power supply
- Power Consumption
  3.3V@1.51A, 5V@3.31A, 12V@9.02A, 5VSB@3.7A (Intel® Xeon® E3-1275 v5 3.60 GHz CPU with 32 GB (four 8GB) 2133 MHz DDR4 memory)
- Operating Temperature: -20°C ~ 60°C
- Storage Temperature: -30°C ~ 70°C
- Operating Humidity: 5% ~ 95%, non-condensing
- Dimensions: 244mm x 305mm
- Weight: GW: 1200g / NW: 700g

Features

- LGA1151 6th generation Intel® Xeon® E3-1200, Core™ i3, Pentium® and Celeron® processor supported
- Dual-channel DDR4 2133 MHz
- Intel® PCIe GbE with Intel® AMT11.0 support
- Support independent triple display with HDMI, DVI and VGA
- Support PCI Express generation 3.0 at 8GT/s I/O bandwidth
- USB 3.0 and SATA 6Gb/s
- Support IPMI 2.0 via iRIS-2400
- IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Packing List

1 x IMBA-C2360-i2 single board computer	1 x One Key Recovery CD
1 x I/O shielding	1 x QIG
2 x SATA cable	1 x Utility CD

Ordering Information

Part No.	Description
IMBA-C2360-i2-R10	ATX motherboard supports 14nm LGA1151 Intel® Xeon® E3 v5 series, Core™ i3, Pentium®, Celeron® processor per Intel® C236, DDR4, triple independent display VGA/DVI-D/HDMI 2.0, dual Intel® PCIe GbE, USB 3.0, SATA 6Gb/s, HD Audio, IPMI 2.0 and RoHS
iRIS-2400-R10	IPMI 2.0 adapter card with AST2400 BMC chip for DDR3 SO-DIMM socket interface
PCIES-2PIMSATA-R10	Peripheral card for flexible I/O, 1 x PCIe Mini, 2 x mSATA expansion
PCIES-USB3-R10	Peripheral card for flexible I/O, USB 3.0 expansion
19800-000075-RS	PS/2 KB/MS cable with bracket, 220mm, P=2.0
19800-003100-100-RS	Dual port USB cable with bracket, 30mm, P=2.54
19800-010500-200-RS	USB 3.0 cable with bracket, 457mm
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P
32205-001203-200-RS	RS-232 cable, 40-pin to four DB-9, 400mm, P=2.54
32205-003800-300-RS	RS-422/485 cable, 200mm, P=2.0
CF-1156A-RS-R11	High performance LGA1155/LGA1156 cooler kit, 1U chassis compatible, 73W
CF-1156C-RS	LGA1155/LGA1156 cooler kit, 1U chassis compatible, 45W
CF-1156D-RS	LGA1155/LGA1156 cooler kit, 1U chassis compatible, 65W
CF-1156E-R11	High performance LGA1155/LGA1156 cooler kit, 95W
DP-DP-R10	DisplayPort to DisplayPort converter board (for IEI iDP connector)
DP-DVI-R10	DisplayPort to DVI-D converter board (for IEI iDP connector)
DP-HDMI-R10	DisplayPort to HDMI converter board (for IEI iDP connector)
DP-LVDS-R10	DisplayPort to 24-bit dual-channel LVDS converter board (for IEI iDP connector)
DP-VGA-R10	DisplayPort to VGA converter board (for IEI iDP connector)
TPM-IN02-R20	20-pin Infineon TPM 2.0 module, software management tool, firmware v5.5