

Industrial Single Board Computer

Mini-ITX Motherboard LV-670



Support Intel® Processor J1900/N2930/E3845 CPU with Onboard VGA, DVI, 2 x LVDS, Display port, HD Audio, Serial ATAII, USB3.0 & 2.0, Gigabit LAN, PCIE X16, PCIE Mini card or mSATA

Form Factor	Mini-ITX motherboard
CPU	Intel® Processor J1900/N2930/E3845, package type FCBGA1170
Memory	2 x DDR3L (support 1.35V) 1066/1333 SO-DIMM up to 8GB
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset with internal timer for 1min/s ~ 255min/s
Power Management	Supports ACPI 5.0 compliant
Serial ATA Interface	2 x serial ATA interface with 300MB/s(3Gb/s) transfer rate (1 x CFAST and 1 x SATAII is for option)
VGA Interface	Intel® Clear Video integrated HD Graphics Technology
DVI Interface	Onboard DVI connector. (DVI and LVDS1 can't be enabled simultaneously)
LVDS Interface	2 x Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply
Display port Interface	Onboard Display port connector. (Display port and LVDS2 can't be enabled simultaneously)
Audio Interface	Realtek ALC262 High Definition Audio Codec
LAN Interface	2 x Intel® I210 Gigabit LAN
GPIO interface	Onboard programmable 8-bit Digital I/O interface.
Extended Interface	One PCIE X16 slot(Only support 1 Lane), 1 x PCIE Mini card or mSATA, 1 x SIM socket (CFAST and mSATA can't be enabled simultaneously)
Internal I/O Port	4 x RS232, 1 x GPIO, 1 x Audio connector, 1 x SMBUS connector, 1 x CRT, 2 x LVDS, 1 x LPC, 2 x USB 2.0(XHCI) and 2 x SATAII
External I/O Port	1 x PS/2 Keyboard/Mouse Port, 1 x RS232, 1 x RS232/422/485, 1 x DVI port, 1 x Display port, 2 x RJ45 LAN ports, 1 x USB 3.0(XHCI)/2.0(EHCI) port, 3 x USB 2.0 ports(EHCI).
External Audio	Line-in, MIC-in, Line-out
Power Requirement	Standard 24-pin ATX power supply or 6~27V full range DC Input
Dimension	170mm x 170mm (L x W)
Temperature	Operating within 0~60 centigrade(for LV-670J and LV-670N serial) Storage within -20~85 centigrade.(forLV-670J and LV-670N serial) Operating within -40~85 centigrade(for LV-670E serial) Storage within -40~85 centigrade.(for LV-670E serial)

Ordering Code

LV-670JIP Intel Celeron Processor J1900 (2M Cache, 2.42GHz), DVI, Display Port, CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card or mSATA, PCIE x16 (only support 1 Lane), SMBUS, GPIO, SIM, LPC

LV-670EIP Intel Atom Processor E3845 (2M Cache, 1.91GHz), DVI, Display Port, CRT, Gigabit LAN,

Taiwan Commate Computer Inc.

19F., No.94, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 22102, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw

COMMELL

Stage For Your Success

Industrial Single Board Computer

LV-67ONIP	Intel Celeron Processor N2930 (2M Cache, 2.16GHz), DVI, Display Port , CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card or mSATA, PCIE x16 (only support 1 Lane), SMBUS, GPIO, SIM, LPC
LV-67OJX2	Intel Celeron Processor J1900 (2M Cache, 2.42GHz), 2 x LVDS , CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card or mSATA, PCIE x16 (only support 1 Lane), SMBUS, GPIO, SIM, LPC
LV-67OEX2	Intel Atom Processor E3845 (2M Cache, 1.91GHz), 2 x LVDS , CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card or mSATA, PCIE x16 (only support 1 Lane), SMBUS, GPIO, SIM, LPC
LV-67ONX2	Intel Celeron Processor N2930 (2M Cache, 2.16GHz), 2 x LVDS , CRT, Gigabit LAN, USB3.0 & 2.0, Serial Port, SATAII, Audio, PCIE Mini card or mSATA, PCIE x16 (only support 1 Lane), SMBUS, GPIO, SIM, LPC

Taiwan Commate Computer Inc.

19F, No.94, Sec.1, Xintai 5th Rd., Xizhi Dist., New Taipei City 22102, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw

Facebook: <https://www.facebook.com/pages/Taiwan-Commate-Computer-Inc/547993955271899>

Twitter: https://twitter.com/Taiwan_Commate



Stage For Your Success