

MPX-350



Features

- Low power consumption and high performance
- One PCIe lane to Dual Gigabit LAN
- Support Mini card PCI-E 1.1 & 1.2 standard specification
- Support WOL and PXE

Product Description

Host Interface	PCI-E
Controller	Intel® I350-AM2 Dual Gigabit Ethernet Controller
Dimension	30.00mm x 50.95mm
Weight	3g
Operating Conditions	
Voltage	3.3V +/-5%
Temperature	0~55°C
Storage Temperature	-40~+85°C

General Specifications

Compliance	IEEE 802.3 Ethernet interface for 1000Base-T, 100Base-TX, and 10Base-T applications (802.3, 802.3u, 802.3ab).
Advanced technologies	I/O Virtualization , WoL, VLAN filtering, PXE remote boot
Transfer Rate	1000 Mb/s, 100 Mb/s, or 10 Mb/s
Support OS	Win7 x32&x64, Win8 x32&x64, Win8.1 x32&x64, Win10 x32&x64, Win server 2012 R2. Linux (kernel versions 2.6.30 or newer)

Ordering Code

MPX-350	PCI Express mini card support dual Gigabit Ethernet (Incl. connection cables and dual RJ45 adapter)
---------	-----------------------------------------------------------------------------------------------------

