


# 03 OMNI-3195-SKU


Industrial Modular Touch Panel Solutions

19" Modular HMI Panel PC with Intel® 6th Generation i5-6300U/C-3955U Processor



## Features

- 19" WXGA (1280 x 1024) TFT LCD Display
- Intel® 6th Generation i5-6300U/C-3955U Processor
- P-CAP or Resistive Touch Support
- Aluminum Design
- IP65 Compliant Front Bezel
- Fanless Operation
- Easily Expandable I/O by AAEON OMNI I/O Modules




## Specifications

System	
Processor	Intel® i5-6300U processor, 2.4 GHz Intel® Celeron® 3955U processor, 2.0 GHz
System Memory	260-pin DDR4 SODIMM x 1, up to 8GB
LCD/CRT Controller	Integrated in processor
Ethernet	Intel® I211, 10/100/1000Base-TX x 1
I/O Port	USB 3.0 type A x 4 SMA Antenna hole x 1 HDMI x 1 DB-9 Type RS-232/422/485 x 2 RJ-45 x 1 for 10/100/1000Base-TXX 3-pin terminal block x1 for 9~30 Vdc power input LED Power on/off switch x1 (Power on = Orange, Power off =N/A)
Storage Disk Drive	2.5" SATA HDD bay x 1
Expansion Slot	Mini card x 1 (Testing Compatibility Only) SIM card x 1 PCIEX 1 connector (AAEON PIN Define)
OS support	Windows® 8.1 Windows® 10 Linux Kernel 2.6.x or above
Mechanical	
Construction	Aluminum design (IP65 Front Frame)
Mounting	Wall/VESA Mount/Desktop (Optional panel mount kits)
Dimension (mm)	18.14" x 16.14" x 2.47" (460.8 x 410 x 62.7 mm)
Gross Weight	19.36 lb (8.8 kg)
Environmental	
Operating Temperature	-20°C ~ 55°C with 0.5 m/s airflow ( Industrial Grade HDD )
Storage Temperature	-4°F ~ 158°F (-20°C ~ 70°C)
Storage Humidity	90% @40°C; non-condensing
Anti-Vibration	1 Grms / 5~ 500Hz / operation – with HDD
Certification	CE/FCC class A
Power Supply	
DC input	DC 9(min) ~ 30 (max) V w/3-pin terminal block, ATX Power function
LCD	
Display type	19" TFT-LCD, LED
Max Resolution	1280(H) x 1024(V)
Max. Colors	16.7M colors
Luminance	350 cd/m <sup>2</sup>
Viewing Angle	170°(H), 160°(V)
Back Light	LED
Back Light MTBF (hours)	—
Touchscreen	
Type	P-CAP/ 5-wire resistive
Light Transmission	P-CAP (≥85%) 5-wire Resistive (80% ± 5%)

# OMNI-3195-SKU

## Dimension

Unit: mm



**OMNI-3195-SKU**

VESA MOUNT:100mm  
 DIM.:460.8\*410\*72.8mm  
 CARTONE DIM. : 661\*206\*496mm  
 NW:6.3KG  
 GW:9.0KG  
 DROP 76mm  
 Cut Out:432\*331 mm(PRE PLUS 3mm)

## Ordering Information

	Part Number	Display Type	Max Resolution	Lumi-nance	View Angle	CPU	LAN	USB 3.0	RS-232/422/485	Storage	RAM	Display	Expansion	Mounting	Power	Operating Temp.	Touch
Panel PC	OMNI-3195HTT-SKU-A1-1010	19" TFT LCD	1280 x 1024	350 cd/m <sup>2</sup>	170°(H) 160°(V)	Intel® i5-6300U, 2.4 GHz	1	4	2	2.5" SATA HDD x 1	DDR4, up to 16GB	HDMI x 1	Mini-Card x 1 (Full Size)	VESA 100/ Panel mount	DC 9~30V	-20°C~55°C with airflow	5-wire Resistive
	OMNI-3195HTT-SKU-A2-1010	19" TFT LCD	1280 x 1024	350 cd/m <sup>2</sup>	170°(H) 160°(V)	Intel® Celeron® 3955U, 2 GHz	1	4	2	2.5" SATA HDD x 1	DDR4, up to 16GB	HDMI x 1	Mini-Card x 1 (Full Size)	VESA 100/ Panel mount	DC 9~30V	-20°C~55°C with airflow	5-wire Resistive
	OMNI-3195HTT-SKU-A3-1010	19" TFT LCD	1280 x 1024	350 cd/m <sup>2</sup>	170°(H) 160°(V)	Intel® i5-6300U, 2.4 GHz	1	4	2	2.5" SATA HDD x 1	DDR4, up to 16GB	HDMI x 1	Mini-Card x 1 (Full Size)	VESA 100/ Panel mount	DC 9~30V	-20°C~55°C with airflow	Projected capacitive
	OMNI-3195HTT-SKU-A4-1010	19" TFT LCD	1280 x 1024	350 cd/m <sup>2</sup>	170°(H) 160°(V)	Intel® Celeron® 3955U, 2 GHz	1	4	2	2.5" SATA HDD x 1	DDR4, up to 16GB	HDMI x 1	Mini-Card x 1 (Full Size)	VESA 100/ Panel mount	DC 9~30V	-20°C~55°C with airflow	Projected capacitive
Panel Kit	OMNI-319DHTT-KIT-A1-1010	19" TFT LCD	1280 x 1024	350 cd/m <sup>2</sup>	170°(H) 160°(V)	—	—	—	—	—	—	—	—	—	—	-20°C~55°C with airflow	5-wire Resistive
	OMNI-319DHTT-KIT-A2-1010	19" TFT LCD	1280 x 1024	350 cd/m <sup>2</sup>	170°(H) 160°(V)	—	—	—	—	—	—	—	—	—	—	-20°C~55°C with airflow	Projected capacitive
CPU BOX Kit	OMNI-SKU-KIT-A1-1010	—	—	—	—	Intel® i5-6300U, 2.4 GHz	1	4	2	2.5" SATA HDD x 1	DDR4, up to 16GB	HDMI x 1	Mini-Card x 1 (Full Size)	VESA 100/ Panel mount	DC 9~30V	-20°C~55°C with airflow	—
	OMNI-SKU-KIT-A2-1010	—	—	—	—	Intel® Celeron® 3955U, 2 GHz	1	4	2	2.5" SATA HDD x 1	DDR4, up to 16GB	HDMI x 1	Mini-Card x 1 (Full Size)	VESA 100/ Panel mount	DC 9~30V	-20°C~55°C with airflow	—

"Note: 1. AAEON OMNI modular display kit only workable for OMNI-BOX Kit 2. RAM not included \* 3. Panel Mount Kit (Optional)

## Packing List

- Phoenix Power Connector
- Product CD with User's Manual (In PDF) and Drivers
- OMNI-3195-SKU

## Optional Accessories

- **AP-0T9789LA1000**  
LCD monitor Stand 230mm, LA-100
- **1702031802**  
Power Cord (US Type)
- **1702031803**  
Power Cord (European Type)
- **170203180E**  
Power Cord (Japanese Type)
- **1255901202**  
19V 120W Power Adapter w/ 3p phoenix block
- **1700021500**  
Remote Switch Cable, 150 cm

## OMNI Module (with AAEON Interface)

- **9741215501**  
WiFi & SIM Card Module (Mini-Card WiFi Module is not Included)
- **9741215502**  
Dual LAN Module
- **9741215503**  
USB / COM / LAN Module
- **9741215504**  
COM Port Module
- **9741215505**  
Isolated COM Port module
- **9741215506**  
DIO Module
- **9741215507**  
CAN Bus Module
- **9741215508**  
Audio Module
- **9741215510**  
HMS Kit
- **9741215511**  
DIO x16 Module

## Wide Temperature DRAM

- **9761215500**  
2GB Wide Temperature DRAM (-40°C ~ 95°C)
  - **9761215501**  
4GB Wide Temperature DRAM (-40°C ~ 95°C)
  - **9761215502**  
8GB Wide Temperature DRAM (-40°C ~ 95°C)
- \*\*Users should select the wide temperature DRAM above and use wide temperature storage devices if the OMNI panel pc is to be operated at over 40°C.